

减速机系列 Speed Reducer

1) Hardened cylinder gear reducer series

硬齿面圆柱齿轮减速机系列



CMEC-ZSY



CMEC-DFY (grade four)



型号 (model): CMEC-ZDY, CMEC-ZDZ

类别 (series): 圆柱齿轮减速机 (硬齿面减速机) 系列

Hardened cylinder gear reducer series

适用范围: 高速轴转速不大于 1500 转/分

齿轮转动圆周速度不大于 20 米/秒

工作环境温度为-40-45℃, 本减速机可正反两个方向转动

Scope of application: rotation rate of high-speed shaft: less than 1500r/min, gear peripheral speed: less than 20m/s. the temperature of working environment is -40-45℃ .The reducer has two rotation directions: the positive and negative direction.

特点: 传动效率高: 单级大于 96.5%。

运转平稳, 噪音低

体积小 重量轻, 寿命长, 承载能力高。

Features: high transmission efficiency (more than 95.5% one single grade)
smooth running and low noise
Small volume, light weight,
Long service life, and high bearing capacity.

2) Middle hard surface cylinder gear reducer series

中硬齿面圆柱齿轮减速机系列



CMEC-QJS



CMEC-QJRS

3) Crane reducer of hardened gear surface series

起重机用硬齿面减速机系列



CMEC-QY3D



CMEC-QJR-D

4) Star gear reducer series 星齿轮减速机系列



CMEC-HGW-L 型立式星齿轮减速器适用条件:

高速轴最高转速不超过 1500r/min, 齿轮圆周速度不超过

15m/s; 工作环境温度: -40~~+45℃

特点: 自重轻, 体积小, 安装方便

传动效率高, 功率范围大(传动功率可达 1.37-500 千瓦)

Scope of application for CMEC-HGW-L type:

The highest speed for shaft is less than 1500r/min

Gear peripheral speed is less than 15m/s,

The temperature of working environment: -40~~+45℃

Features: light weight, small volume, simple installation

high transmission efficiency, large load power (transmission power:

1.37-500 KW) .

PARTIAL PRODUCTS 部分产品



CMEC-HNY 星轮减速机
star gear reducer



CMEC-HNW 星轮减速机
star gear reducer



CMEC-KJY 星轮减速机
Star gear reducer



CMEC-HJW 星轮减速机
star gear reducer



ZD.ZL.ZS 型齿轮减速机
Gear reducer



ZQD 型大速比齿轮减速机
High speed ratio gear reducer



ZSC 型圆柱齿轮减速机
Cylinder gear reducer



ZQ.JZQ 型齿轮减速机
Gear reducer