

ELECTRIC HOIST CATALOGUE



Features:

upper and lower limit device
Anti-reverse winding device
Emergency stop switch
Thermal protection terminal
Protection class IP54.

Method of use(PA100D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	180	
Rated lifting weight(kg)	50	100
Lifting speed(m/min)	8	4
Lifting height(m)	8	4
Qty/CTN(PCS)	4	
Packing dimension(cm)	41*30*32	
G.W./N.W.(kg)	21/20	



Features:

Upper and lower limit device
 Anti-reverse winding device
 Emergency stop switch
 Thermal protection terminal
 Protection class IP54.

Method of use(PA200D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	450	
Rated lifting weight(kg)	100	200
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	46*36*16	
G.W./N.W.(kg)	21/20	



Features:

Upper and lower limit device
 Anti-reverse winding device
 Emergency stop switch
 Thermal protection terminal
 Protection class IP54.

Method of use(PA250D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	500	
Rated lifting weight(kg)	125	250
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	46*36*16	
G.W./N.W.(kg)	21/20	

Hebei-CMEC Metals & Machinery I/E Corp.



Features:

- upper and lower limit device
- Anti-reverse winding device
- Emergency stop switch
- Thermal protection terminal
- Protection class IP54.

Method of use(PA300D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	550	
Rated lifting weight(kg)	150	300
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	46*36*16	
G.W./N.W.(kg)	22/21	



Features:

- upper and lower limit device
- Anti-reverse winding device
- Emergency stop switch
- Thermal protection terminal
- Protection class IP54.

Method of use(PA400D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	750	
Rated lifting weight(kg)	200	400
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	52*39*18	
G.W./N.W.(kg)	33/31	



Features:

Upper and lower limit device

Anti-reverse winding device

Emergency stop switch

Thermal protection terminal

Protection class IP54.

Method of use(PA500D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	900	
Rated lifting weight(kg)	250	500
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	52*39*18	
G.W./N.W.(kg)	34/32	



Features:

Upper and lower limit device
 Anti-reverse winding device
 Emergency stop switch
 Thermal protection terminal
 Protection class IP54.

Method of use(PA600D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	1050	
Rated lifting weight(kg)	300	600
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	52*41*17	
G.W./N.W.(kg)	36/34	



Features:

Upper and lower limit device
 Anti-reverse winding device
 Emergency stop switch
 Thermal protection terminal
 Protection class IP54.

Method of use(PA800D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	1350	
Rated lifting weight(kg)	400	800
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	52*44*17	
G.W./N.W.(kg)	38/36	



Features:

Upper and lower limit device

Anti-reverse winding device

Emergency stop switch

Thermal protection terminal

Protection class IP54.

Method of use(PA1000D)	Single hook	Double hook
Rated volt(V)	220/230	
Input power(W)	1600	
Rated lifting weight(kg)	500	999
Lifting speed(m/min)	8	4
Lifting height(m)	12	6
Qty/CTN(PCS)	1	
Packing dimension(cm)	52*24*33	
G.W./N.W.(kg)	34/32	